



Castrol EDGE Professional LL IV FE 0W-20

Boosted with TITANIUM FST™ - Strength for Maximum Performance

Description

Castrol EDGE Professional, boosted with *TITANIUM FST™*, provides outstanding oil strength for today's engines that work harder, with higher pressures than ever before.

Castrol EDGE Professional is our strongest and most advanced range of engine oils.

Castrol EDGE Professional with *TITANIUM FST™*: helping your engine perform at its best.

Castrol EDGE Professional is now certified CO₂ neutral according to the highest global standards. Engineered with micro filtration in order to meet Castrol Professional's quality standard and verified using our Optical Particle Measurement System to guarantee product quality.

Application

Castrol EDGE Professional LL IV FE 0W-20 is approved for use in VW Group vehicles that require a VW 508 00 / 509 00 specification 0W-20 lubricant.

Advantages

Castrol EDGE Professional LL IV FE 0W-20 gives you the confidence to demand maximum engine performance from today's latest technology, highly engineered engines that operate with tighter tolerances, requiring a high level of protection and low viscosity oils.

Castrol EDGE Professional LL IV FE 0W-20:

- Maximises short and long term engine performance
- Reduces engine deposits to help maximise engine response
- Delivers complete protection across a variety of engine speeds, conditions and temperatures
- Sustains maximum performance even when under pressure
- Independently proven to improve engine efficiency
- Delivers unsurpassed levels of protection across a variety of driving conditions and temperatures
- Reduces diesel engine deposits to help maximise engine response
- Delivers the highest levels of fuel efficiency
- Excellent performance at low temperatures

Typical Characteristics

Name	Method	Units	Castrol EDGE Professional LL IV FE 0W-20
Density @ 15C, Relative	DIN 51757	g/ml	0.84
Viscosity, Kinematic 100C	DIN 51562	mm ² /s	8.1
Viscosity, CCS -35C (0W)	DIN 51377	mPa.s (cP)	3900
Viscosity, Kinematic 40C	DIN 51562	mm ² /s	44
Viscosity Index	ISO 2909	None	164
Pour Point	ASTM D97	°C	-66
Ash, Sulphated	DIN 51575	% wt	0.75
Flash Point, PMCC	ASTM D93	°C	209

Product Performance Claims

VW 508 00/509 00

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol EDGE Professional LL IV FE 0W-20

21 Jun 2016

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com